



## 150mm KERB AND GUTTER

SCALE 1 : 10

### NOTES:

1. CONCRETE STRENGTH SHALL BE 25MPa WITH 14mm AGGREGATE, COMPLYING WITH THE REQUIREMENTS OF AS1379.
2. SHRINKAGE CONTROL JOINTS (TOOLED JOINTS) SHALL BE PROVIDED AT 3.0m MAXIMUM SPACINGS (20mm DEPTH TO PRODUCE NEAT GROOVE NOT LESS THAN 5mm WIDE).
3. ALL KERBING SHALL COMPLY WITH AS2876.
4. BACKFILL BEHIND KERB AS SPECIFIED ON DESIGN DRAWINGS.
5. RECYCLED QUARRIED PRODUCTS SHALL BE FREE FROM GLASS AND CERAMIC DEBRIS.



DRAWING FILE  
LOCATION  
T:\AUTOCAD BLOCKS\2010\150  
KERB 375WT 40FALL + BASE  
(M1242).dwg

COORDINATOR  
DESIGN  
B. MORIAS  
01.11.22

EDITED  
G. FERTEKLIS  
01.11.22  
DRAWN  
J. CURSARO  
23.02.11  
DESIGNED  
J. CURSARO  
23.02.11

### STANDARD DETAILS

**150mm KERB & GUTTER**  
**375mm TRAY WITH 40mm CROSS**  
**FALL** SCALE AS SHOWN

CITY OF CHARLES STURT

SHEET  
**1** of **1**  
TRIM No.  
**06/59646**  
DRAWING No.  
**M.1242**