

ANGLE OF FACE TO
MATCH KERB PROFILE

100mm x 100mm x 5mm SHS
HOT DIP GALVANISED.

10mmØ M.S ROD, 150mm LONG
WITH 30mm COG.

GAP TO BE SEALED WITH "PARFIX
ROOF, GUTTER & CONCRETE" SEALANT
(OR SIMILAR APPROVED) ON BOTH SIDES

DRAINAGE OUTLET KERB INSERT (UPRIGHT KERB)

SCALE 1 : 5

NOTES:

1. THE ENTIRE KERB OUTLET ASSEMBLY SHALL BE HOT DIP GALVANISED.
2. THE KERB OUTLET SHALL SIT FLUSH WITH TOP OF KERB (UNLESS NOTED OTHERWISE.)
3. THE KERB OUTLET SHALL BE SET BACK FROM FACE OF KERB BY A MINIMUM OF 25mm TO ENSURE THAT THERE ARE NO EDGES PROTRUDING PAST FACE OF KERB.
4. THIS DRAINAGE OUTLET SHALL ONLY BE USED FOR 100mm HIGH KERB & GUTTER.



DRAWING FILE
LOCATION
T:\AUTOCAD
BLOCKS\2010\STORMWATER
DRAINAGE OUTLET - TYPE 2
(M1577).dwg

COORDINATOR
DESIGN
B. MORIAS
21.11.23

EDITED
G. FERTEKLIS
21.11.23
DRAWN
G. FERTEKLIS
11.11.22
DESIGNED
G. FERTEKLIS
11.11.22

STANDARD DETAILS

STORMWATER DRAINAGE OUTLET (TYPE 2)

SCALE AS SHOWN

CITY OF CHARLES STURT

SHEET
1 of 1

TRIM No.
23/7882

DRAWING No.
M1577