



## SPOONDRAIN

SCALE 1 : 10

### NOTES:

1. CONCRETE STRENGTH SHALL BE 25MPa WITH 14mm AGGREGATE, COMPLYING WITH THE REQUIREMENTS OF AS1379.
2. SHRINKAGE CONTROL JOINTS (TOOLED JOINTS) SHALL BE PROVIDED AT 3.0m MAXIMUM SPACINGS (20mm DEPTH TO PRODUCE NEAT GROOVE NOT LESS THAN 5mm WIDE).
3. RECYCLED QUARRIED PRODUCTS SHALL BE FREE FROM GLASS AND CERAMIC DEBRIS.



DRAWING FILE LOCATION  
T:\AUTOCAD BLOCKS\2010+SPOONDRAIN 750 40 TRAY (M1499).dwg

COORDINATOR DESIGN  
B. MORIAS  
07.11.22

EDITED  
G. FERTEKLIS  
07.11.22  
DRAWN  
J. CURSARO  
07.04.11  
DESIGNED  
J. CURSARO  
07.04.11

STANDARD DETAIL  
**SPOONDRAIN**  
750 WIDE WITH 40 TRAY

SCALE AS SHOWN

CITY OF CHARLES STURT

SHEET  
**1** of **1**

TRIM No.  
**14/178076**

DRAWING No.  
**M. 1499**