



PERMEABLE PAVERS - FOOTPATH / INDENTED PARKING

SCALE 1 : 10

NOTES:

1. COLOUR OF PAVER TO BE APPROVED BY COUNCIL.
2. THIS STANDARD APPLIES TO FOOTPATH AND LIGHT TRAFFIC INDENTED PARKING APPLICATIONS AND SHALL NOT BE USED FOR DRIVEWAYS AND CROSSOVERS.

SIEVE SIZE (mm)	GRADED PERMEABLE GRANULAR BASE (%)
26.5	100
19	95-100
13.2	70-93
9.5	55-85
4.75	20-75
2.36	10-50
1.18	0-25
0.6	0-12
0.425	-
0.3	0-8
0.15	0-6
0.075	0-5

PERMEABLE PAVEMENT GRADING TABLE



DRAWING FILE LOCATION
T:\AUTOCAD BLOCKS\2010\PERMEABLE PAVERS - FOOTPATH AND INDENTED PARKING (M1583).dwg

COORDINATOR DESIGN
B. MORIAS
25.01.23

EDITED
G.FERTEKLIS
25.01.23
DRAWN
G.FERTEKLIS
17.03.22
DESIGNED
G.FERTEKLIS
17.03.22

STANDARD DETAILS

PERMEABLE PAVERS FOOTPATH / INDENTED PARKING

SCALE AS SHOWN

CITY OF CHARLES STURT

SHEET
1 of 1

TRIM No.
23/16157

DRAWING No.
M1583